

commBOX Interactive Pulse V3 Specs

MODELS



Pulse 55




Pulse 65



Pulse 86

SKU	CBIP55	CBIP65	CBIP86
Resolution	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz	UD 3840x2160 @60Hz
Brightness	350cd/m2	350cd/m2	350cd / m2
Glass	Anti-glare	Anti-glare	Anti-glare
Viewing Angle	178°	178°	178°
Response Time	< 30ms	6ms	8ms
Operating Humidity	10- 90%	10- 90%	10- 90%
Operating Con	0C to 40C	0C to 40C	0C to 40C
Power Req	AC 100 to 240V, 50/60Hz	AC 100 to 240V, 50/60Hz	AC 100 to 240V, 50/60Hz
Power Max	250W	300W	500W
Power Standby	<0.5W	<0.5W	<0.5W
Touch	20 points , 1mm	20 points , 1mm	20 points , 1mm
Touch Technology	PCAP	PCAP	PCAP
Android	7.0, 2GB RAM, 16GB Storage	7.0, 2GB RAM, 16GB Storage	8.0, 4GB RAM, 32GB Storage
VESA	400 x 200, M8	600 x 400, M8	800 x 600, M8
Speakers	10W x 2 + 15W Sub	10W x 2 + 15W Sub	10W x 2 + 15W Sub
Input/Output	OPS PC Slot, VGA In, 2 x HDMI In, 1 x HDMI Out, 1 x AV In, 1 x Audio In, 1 x Audio Out, Optical In, 2 x USB Touch, 4 x USB 2.0, 1 x USB 3.0, Ethernet, RS232	OPS PC Slot, VGA In, 2 x HDMI In, 1 x HDMI Out, 1 x AV In, 1 x Audio In, 1 x Audio Out, Optical In, 2 x USB Touch, 4 x USB 2.0, 1 x USB 3.0, Ethernet, RS232	OPS PC Slot, VGA In, 3 x HDMI In, 1 x HDMI Out, 1 x AV In, 1 x Audio In, 1 x Audio Out, Optical In, 2 x USB Touch, 3 x USB 2.0, 3 x USB 3.0, Ethernet, RS232



1269 (W) x 747 (H)
x 87 (D)mm

Screen Dims

Screen Weight

29kg

Packed Dims

1428 (W) x 845 (H)
x 220 (D)mm

Packed Weight

40.6kg



1493 (W) x 872 (H)
x 88 (D)mm

1697 (W) x 1039 (H)
x 220 (D)mm

53kg

Remote (w\Batteries),
HDMI Cable, Slot-in WIFI
module, USB touch cable,
power cord & wall bracket

Accessories

Warranty

3 Year Onsite
(Optional 4 or 5 Year)



1962 (W) x 1136 (H)
x 85 (D)mm

2166 (W) x 1336 (H)
x 280 (D)mm

93.5kg

Remote (w\Batteries), HDMI Cable,
Slot-in WIFI module, USB touch cable,
2 x Active Stylus Pen w/ charging box,
power cord & wall bracket.

3 Year Onsite
(Optional 4 or 5 Year)