

Product Information Sheet

P474WG - Professional Projector



Brighten up your lectures and meetings

The NEC P474WG brings brightness of up to 4,700 ANSI lumen to your meeting and learning spaces. Enjoy smooth operation over five years* with low maintenance, long lamp life and the NEC patented LCD panel dust protection. The NEC P474WG is the perfect replacement device for preceding models because it offers the same mounting options and with its wide zoom range, it is easy to adjust the projection to the existing screen. LCD technology delivers natural colours with a high contrast whilst the wide horizontal and vertical lens shift offers broad flexibility in installation. With its low power consumption, the NEC P474WG offers a low total cost of ownership (TCO) and helps you to reduce your carbon footprint.

For more efficient and collaborative meetings and lectures, add NEC's MultiPresenter option to share content from up to 16 devices! No additional power source is needed as the stick is powered via the USB slot.

*see warranty below for more details.

Benefits

Affordable Large Screen projection – ideal for larger corporate or education venues and auditoriums.

Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

High brightness – for best performance in bright ambient light

Cost Saving Device Management – save effort whilst administrating all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Minimized cost of ownership – due to long lamp life and filter exchange intervals.

Peace of Mind – with future-proof connectivity.

Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Product information

Product Name	P474WG
Product Group	Professional Projector
Order Code	NP-P474WG

Image

Projection Technology	3LCD Technology
Native Resolution	1280 x 800 (WXGA)
Contrast Ratio ¹	18,000:1
Brightness ¹	5,200 Centre, 4,700 Eco Off, 4,050 Normal Eco, 3,050 Eco
Lamp	330 W UHP AC
Lamp Life [hrs]	4000 (8000 Eco Mode)
Lens	F=1.7 to 2.2, f=17.4 to 29.0mm
Lens shift	H:±0.15, V:+0.55,-0
Keystone correction	+/- 20° manual horizontal / +/- 30° manual vertical
Projection Factor	1.2 – 2 : 1
Projection Distance [m]	0.8 – 12.9
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 76 / 30"
Zoom	1 - 1.7; Manual
Focus Adjustment	Manual
Supported Resolutions	Up to 1280 x 800 (WXGA)
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz); Vertical: 50 – 120 Hz

Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15 pin Output: 1 x Mini D-sub 15 pin
Digital	Input: 1 x HDBaseT; 2 x HDMI™ (Deep Color, Lip sync) with HDCP
Video	Input: 1 x RCA
Audio	Input: 1 x 3.5 mm Stereo Mini Jack for Computer analog; 1 x RCA Stereo for Video and S-Video; 2 x HDMI audio Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	1 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select
----------------	---

Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	418 (Normal) / 280W /2.0 (Network Stand-by) / 0.16W (stand-by)

Mechanical

Dimensions (W x H x D) [mm]	420 x 133 x 322 (without lens and feet)
Weight [kg]	4.8

Fan Noise [dB (A)] 34 / 37 (Eco / Normal)

Environmental Conditions

Operating Temperature [°C] 5 to 40
 Operating Humidity [%] 20 to 80 non-condensing
 Storage Temperature [°C] -10 to 50
 Storage Humidity [%] 20 to 80 non-condensing

Ergonomics

Safety and Ergonomics CE; ErP; RoHS; TÜV GS ;RCM
 Speakers [W] 1 x 20 (mono)

Additional Features

Special Characteristics Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Contrast Ratio 18,000:1 with Iris; Control ID Function; DICOM Simulation; Direct Power-Off Function; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Lens Shift (vertical 0 max/55 max, horizontal ± 15 max.); Magnify; Manual Wall Color Correction; NaViSet Administrator 2; Off-Timer; Optional User Logo; OSD with 27 languages; Password Security System; Pincushion Correction; Quick Start; Test Pattern; Unique Power Saving Functions; Virtual Remote for direct PC control

Green Features

Energy Efficiency 0.4W Power save mode; Auto ECO Mode; Green one touch ECO and AV mute button
 Ecological Materials Downloadable manuals; ECO packaging
 Ecological Standards ErP compliant; RoHs compliant

Warranty

Projectors 5 years conditional warranty
 Light Source 6 months or 2000 hours (whichever comes first) applies to the lamp.

Shipping Content

Shipping Contents IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Projector; Quick Setup Guide; Users Manual; Utility software

Optional Accessories

Optional Accessories Cable Cover (NP12CV); Lamp (NP44LP); MultiPresenter Stick; Wireless LAN Module NP05LM4

¹ Compliance with ISO21118-2012



For more information:

www.nec.com.au contactus@nec.com.au 131 632

Corporate Headquarters (Japan) NEC Corporation www.nec.com **Australia** NEC Australia Pty Ltd www.nec.com.au **North America (USA)** NEC Corporation of America www.necam.com **Asia Pacific (AP)** NEC Asia Pacific www.sg.nec.com **Europe (EMEA)** NEC Enterprise Solutions www.nec-enterprise.com

v.12.04.19 | P474WG

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2019 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

