

MAXHUB

Product Spec

1. Product Feature



2. Interface

Type-C	1
Button	1

3. Function

Maximum connection distance	12m
Operating Systems Supported	Windows7/8/10; mac OS 10.10~10.13;Linux
Operating frequency	2.4GHz, 5GHz
Transmission Delay	The minimum delay in the laboratory environment is 90ms (the actual situation is affected by the use environment)
Frame rate	Windows7: 1920 × 1080@30fps/1366 × 768@30fps Windows8(8.1)/OSX: 1920 × 1080@30fps/1366 × 768@30fps Windows10:

MAXHUB

	1920 × 1080@30fps/1366 × 768@30fps (the actual situation is affected by the use environment)
--	---

4. Power

Power Requirements	5V DC
Power Consumption	2.5W

5. Physical Specifications

Dimension L × H × D	171.2 × 77 × 21.3mm
Dimension (package) L × W × H	210 × 111 × 44mm
Net Weight	0.1kg
Gross Weight	0.25kg

6. Accessories

USB Adapter	× 1
User Manual	× 1

7. Environmental Conditions

Operation Temperature	0°C – 40°C
Operation Humidity	10% – 90%RH
Storage Temperature	-20°C – 60°C
Storage Humidity	10% – 90%RH

8. Statement

The product pictures of this specification only indicate that there may be slight

MAXHUB

difference in product effects (included but not limited to appearance, color and size). Please refer to the product.

Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information.

No special notice will be given if necessary.

MAXHUB