

newline



USB Type-C
With Power



Antimicrobial
Surface



Secure
Android 11 OS



Eco-friendly
Proximity Sensor



Better
Connectivity



Superior Capacitive
Touch (PCAP)



Tiltable 4K Wide
Angle Camera



Compatible
with all Devices

ALL-IN-ONE COLLABORATION SOLUTION

Redefine collaboration with the Newline Z Series, an ultra-high definition display that provides an immersive audio-visual experience for your meeting rooms and huddle spaces. No matter where you sit, the 4K display provides a crystal clear image and a 178° viewing angle.

Start meetings faster with the plug and play design of the Z Series. Plug in your laptop through the USB Type-C cable and start presenting, all while the Z Series keeps your laptop charged. Keep your panel and data secure with the embedded Android 11 OS that also provides customization options like unique user profiles. A built-in Wi-Fi 6 module offers greater connectivity and compatibility for securely connecting multiple devices. The Z Series comes equipped with a Proximity Sensor, and will sleep/reawaken automatically based on human presence in the room.

The UC ready Z series display comes with an onboard computer (OPS) integrated into the display, no extra devices needed, a flexible 4K wide angle camera, and a built-in 8 mic array for the perfect all in one collaboration solution.

Build a more dynamic collaborative space with the Z Series.

Newline Z Series includes the following software solutions

CAST

BROADCAST

DISPLAY MANAGEMENT PLUS

Z Series

Model	UC Ready Version	Non-UC Version
SKUs	55": TT-5522Z-UC 65": TT-6522Z-UC 75": TT-7522Z-UC 86": TT-8622Z-UC	55": TT-5522Z 65": TT-6522Z 75": TT-7522Z 86": TT-8622Z
4K Camera Module	Yes	No
OPS On-Board Computer	Yes	No



Modular 4K Camera - UC Ready Z Series Only



OPS On-Board Computer - UC Ready Z Series Only

SKUs	55": TT-5522Z-UC 65": TT-6522Z-UC 75": TT-7522Z-UC 86": TT-8622Z-UC
Camera Module	
Camera Resolution	4K@ 30 Hz /UHD
Field of View	120° FOV Lenses
IR Camera	352 x 352 / 30 fps
Camera Tile Range	15°
OPS On-Board Computer	
CPU	i7-8565U, 8M Cache, up to 4.60 GHz
GPU	Intel HD Graphics 620
RAM	8GB
Hard Disk	256GB SATA3 SSD
USB 2.0	2
USB 3.0	2
USB Type C	1
LAN	1
HDMI Out	1
Microphone In	1
Line Out	1
Built-in WiFi	802.11b/g/n/ac
OS	Win 10 Pro 64bit (other OS optional)
RAM Upgrades	Up to 32GB

Z Series

Model	TT-5522Z TT-5522Z-UC	TT-6522Z TT-6522Z-UC	TT-7522Z TT-7522Z-UC	TT-8622Z TT-8622Z-UC
Display				
Screen Size	55"	65"	75"	86"
Display Area	47.6 x 26.8 in	56.2 x 31.6 in	64.9 x 36.5 in	74.6 x 41.9 in
Backlight	LED	LED	LED	LED
Resolution	3840 x 2160 pixels (4K)	3840 x 2160 pixels (4K)	3840 x 2160 pixels (4K)	3840 x 2160 pixels (4K)
Display Ratio	16:9	16:9	16:9	16:9
Brightness	400nit	400nit	400nit	400nit
Display Colors	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)	1.07 billion (8 bit)
Contrast Ratio	4000:1	4000:1	4000:1	4000:1
Response Time	8 ms	8 ms	8 ms	8 ms
Viewing Angle	178°	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Continuous Run Time	24/7	24/7	24/7	24/7
Speakers				
Position	Top-Front	Top-Front	Top-Front	Top-Front
Max Power Output	(2) 20W	(2) 20W	(2) 20W	(2) 20W
Output S.PL	0dB~ -10dB	0dB~ -10dB	0dB~ -10dB	0dB~ -10dB
Microphone				
Mic Position	8-mic array - upper front	8-mic array - upper front	8-mic array - upper front	8-mic array - upper front
Distance	26 ft	26 ft	26 ft	26 ft
Power				
Max Power Consumption	≤250W (Standby ≤0.5W)	≤400W (Standby ≤0.5W)	≤500W (Standby ≤0.5W)	≤550W (Standby ≤0.5W)
Working Voltage	AC100-240V Max 2.5A	AC100-240V Max 4.0A	AC100-240V Max 5.0A	AC100-240V Max 5.5A
Touch				
Glass Surface Technology	Tempered Glass	Tempered Glass	Tempered Glass	Tempered Glass
Touch Points	20 Points / optional Windows 40 Point	20 Points / optional Windows 40 Point	20 Points / optional Windows 40 Point	20 Points / optional Windows 40 Point
Touch Sensor	PCAP (Projected Capacitive Touch)	PCAP (Projected Capacitive Touch)	PCAP (Projected Capacitive Touch)	PCAP (Projected Capacitive Touch)
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger	Stylus or Finger
Transportation/Storage				
Storage Temp/Humidity	14°F - 113°F / 0% - 90%	14°F - 113°F / 0% - 90%	14°F - 113°F / 0% - 90%	14°F - 113°F / 0% - 90%
Working Temp/Humidity	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
VESA Mount	400x400mm	600x400mm	800x400mm	800x400mm
Outline Dimension	50.3 in. x 31.4 in. x 3.1 in.	58.9 in. x 36.2 in. x 3.3 in.	67.7 in. x 41.1 in. x 3.3 in.	77.4 in. x 46.6 in. x 3.3 in.
Weight	61.7 lbs	79.3 lbs	110.2 lbs	132.3 lbs
Embedded Operating System				
SoC Chipset	Amlogic 311D2	Amlogic 311D2	Amlogic 311D2	Amlogic 311D2
RAM	8 G	8 G	8 G	8 G
Flash Memory	64GB	64GB	64GB	64GB
Android Version	11.0	11.0	11.0	11.0
Multimedia Files Supported	Image: JPEG, BMP, PNG Video: MPEG1, MPEG2, MPEG4, Sorenson H.263, H.263, H.264, HEVC/H.265, MVC, AVS, AVS+, WMV3, VC1, Motion JPEG, VP8, VP9, RV30/RV40 Audio: MPEG1/2 @LAYER1;@LAYER2;@LAYER3, EAC3, ACC-LC, HE-AAC, VORBIS, LPCM, IMA-ADPCM, MS-ADPCM, G711 A/MU-LAW, LBR(COOK), FLAC			
Ports				
Side Inputs/Outputs	USB Type-C (PD 65W/100W Optional) x 1, HDMI IN 2.0 x 1, USB Type-B (Touch) x 1, USB 3.0 Type-A x 1, Microphone In x 1			
Rear Inputs/Outputs	HDMI IN 2.0 x 2, DisplayPort 1.2 x 1, USB Type-B (Touch) x 3, USB 3.0 Type-C (no PD) x 1, USB 3.0 Type-A x 2, USB 3.0 Type-A to Android x 1, HDMI OUT 2.0 x 1, RS232 x 1, RJ45 (Gigabit) IN x 1, RJ45 (Gigabit) OUT x 1, SPDIF x 1, OPS x 1, Audio Line out x 1, WIFI module x 1, Proximity Sensor x 1			