


## Key Features

- Wireless presentation for enhanced efficiency
- Single USB-C cable for 65W power delivery
- 24/7 video playback for continuous communication
- Remote device management with myViewBoard Manager
- ProAV compatibility with Crestron, Extron, and AMX



## Product **Description**

With stunning 4K Ultra HD resolution, high brightness, and landscape and portrait modes, the CDE30 Series offers continuous and sustainable 24/7 display for both corporate and campus communication. Purpose-engineered for ease of use, the display is equipped with a Quad Core SoC to run multiple operations seamlessly, and its USB-C one-cable solution sorts for effortless connection with external devices. Designed for easy-to-operate continuous multimedia playback, the CDE30 Series offers cable-free screen casting and screen sharing through myViewBoard Display and vCast, which also supports Airplay and Chromecast. Remote management via the intuitive myViewBoard Manager makes changing content, broadcasting, and software updates a breeze. Available in six sizes ranging from 43" to 98", the CDE30 Series features HDMI input and output for seamless tiling of up to 9 screens, meeting the communication needs of any campus, corporate, or retail space.



- 1. Power Switch
- 2. AC IN
- 3. SPDIF
- 4. LAN 5. USB 2.0
- 6. USB 3.0
- 7. RS-232

- 8. HDMI OUT
- 9. HDMI 2
- 10. HDMI 1(ARC)
- 11. USB-C
- 12. Control Panel
- 13. Speaker
- 14. WiFi Slot

15. VESA® Wall Mount (200x200mm)

31/10/2024, 12:12 pm 1 of 2

**DISPLAY** 

Panel Size: 43"

TFT LCD Module. VA type, Type/ Tech:

DLED backlight

941.184(H) × 529.416(V) Display Area (mm):

(42.5" diagonal)

Native Resolution: 3840 x 2160

Aspect Ratio: 16:9

Colors: 1.07G (8bits + FRC-)

Brightness: 450 nits (typ.)

1200:1 (typ.), 5000:1 (DCR Contrast Ratio:

enabled)

Response Time: 6.5ms

H = 178, V = 178 typ. Viewing Angles:

Backlight Life: 50,000 hours

Anti-Glaire, 3H hardness, Surface Treatment:

Haze 25%

9.9/9.9/9.9/9.9 mm (L/R/T/ Bezel:

Orientation: Landscape & Portrait

**PLATFORM** 

Processor: Quad-core ARM Cortex A55

RAM: 4GB Storage: 32GB

**INPUT** 

2.1x2 (3840x2160 @60Hz, HDMI: HDMI 1 supports ARC)

RS-232: WiFi Slot:

OUTPUT

2.0 x1 (3840x2160@60Hz HDMI:

SPDIF: x 1

LAN

RJ45:

USB

2.0 x 1, 3.0 x 1 Type A:

x1 ( (DP1.2, PD 65W, Type C: USB2.0, 100M ethernet)

**SPEAKERS** 

10W x2

**EMBEDDED OS** 

Android 11

**POWER** 

Voltage: 100-240 VAC +/- 10% Consumption: 64 W(typ.) < 0.5W(off)

**OPERATING CONDITIONS** 

Temperature (º C): 0 to 40°C 10%-90% RH Humidity:

**OPERATING HOURS** 

7/24

**DIMENSIONS (WXHXD)** 

37.98 x 21.75 x 2.81 Physical (inch / mm): in/964.6 x 552.5 x 71.4mm

41.57 x 26.46 x 6.14 Packaging (inch / mm): in./1056 x 672 x 156 mm

WEIGHT

21.83lbs/9.9kg Net (lb / kg): Gross (lb / kg): 30.53lbs/13.85kg

**REGULATIONS** 

cTUVus, FCC/ICES003, Energy star 8.0, EPEAT, Mexico NOM, Mexico Energy, EMC/CE, CB, EAC, UkrSEPRO, RCM, LBL, Flicker free, Green BOM, RoHS, ErP, REACH, SCIP, WEEE, Annex I, Annex II, TPCH, Packing waste, CA65

**PACKAGE CONTENTS** 

1. Remote Control with batteries

2. Quick Start Guide 3. Power Cables

4. HDMI cable 5. USB-C cable

6. Wall Mount Screw x 4

7. RS232 adapter

8. Compliance statement

Copyright © ViewSonic Corporation 2000-2024, All rights reserved